



SDS No. 0235011-US2  
Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

## SAFETY DATA SHEET

### 1. Identification

**Product Identifier** Suzuki Super Long Life Coolant  
**Other means of identification** Antifreeze/Coolant  
**Recommended use of the chemical and restrictions on use** Engine Coolant

#### Supplier Information

**Name** CCI CORPORATION  
**Address** 12 Shinhasama, Seki, Gifu 501-3923, JAPAN  
**Phone Number** +81-(0)575-24-4744  
**FAX Number** +81-(0)575-24-4447

### 2. Hazard identification

#### GHS classification of the substance/mixture and any national or regional information

<b>Physical hazards</b>	Explosives	-
	Flammable Gases	-
	Flammable Aerosols	-
	Oxidizing Gases	-
	Gases Under Pressure	-
	Flammable Liquids	Not classified
	Flammable Solids	-
	Self-Reactive Substances	-
	Pyrophoric Liquids	Not classified
	Pyrophoric Solids	-
	Self-Heating Substances	Classification not possible
	Substances Which in Contact with Water Emit Flammable Gases	-
	Oxidizing Liquids	Classification not possible
	Oxidizing Solids	-
	Organic Peroxides	-
	Substances Corrosive to Metal	Not classified
	<b>Health hazards</b>	Acute Toxicity(Oral)
Acute Toxicity(Dermal)		Classification not possible
Acute Toxicity(Inhalation-Gases)		-
Acute Toxicity(Inhalation-Vapors)		Classification not possible
Acute Toxicity(Inhalation-Dusts)		-
Acute Toxicity(Inhalation-Mists)		Classification not possible
Skin Corrosion / Irritation		Category 3

SDS No. 0235011-US2  
 Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

	Serious eye damage / Eye irritation	Category 2
	Respiratory Sensitization	Classification not possible
	Skin Sensitization	Classification not possible
	Germ Cell Mutagenicity	Classification not possible
	Carcinogenicity	Classification not possible
	Reproductive Toxicology	Category 1
	Specific target organ toxicity single exposure	Category 1 (Central nerves, Kidney, Heart, Respiratory)
	Specific target organ toxicity repeated or prolonged exposure	Category 1 (Central nerves, Respiratory, Heart)
	Aspiration hazard	Classification not possible
<b>Environmental Hazards</b>	Acute Aquatic Toxicity	Category 3
	Chronic Aquatic Toxicity	Not classified
<b>GHS Label elements</b>		
<b>Hazardous pictograms</b>		
<b>Signal words</b>	Danger	
<b>Hazard statements</b>	<p>Causes serious eye irritation</p> <p>Causes mild skin irritation</p> <p>May damage fertility or the unborn child</p> <p>Causes damage to organs (Central nerves, Kidney, Heart, Respiratory)</p> <p>Causes damage to organs (Central nerves, Respiratory, Heart) through prolonged or repeated exposure.</p> <p>Harmful to aquatic life</p>	
<b>Precautionary statements</b>		
Prevention	<p>Wash contacted body parts thoroughly after handling.</p> <p>Wear protective gloves/protective clothing/eye protection/ face protection.</p> <p>Obtain special instructions before use.</p> <p>Do not handle until all safety precautions have been read and understood.</p> <p>Use personal protective equipment as required.</p> <p>IF exposed or concerned: Get medical advice/attention.</p> <p>Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>Do not eat, drink or smoke when using this product.</p> <p>Avoid release to the environment.</p>	
Response	<p>Call a POISON CENTER/doctor/physician if you feel unwell.</p> <p>If skin irritation occurs: Get medical advice/attention.</p>	

SDS No. 0235011-US2  
 Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice / attention.

If exposed: Call a POISON CENTER or doctor/physician.

Get medical advice/attention if you feel unwell.

Storage

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3. Composition/information on ingredients

Component	CAS No.	Content %
Ethylene Glycol	107-21-1	45-55
Water	7732-18-5	45-55
Additives	Proprietary	<5

### 4. First aid measures

**Ingestion** If victim is conscious and able to swallow, quickly have victim drink water or milk to dilute. Do NOT give sodium bicarbonate, fruit juices or vinegar. NEVER give anything by mouth if victim is unconscious or having convulsions. Induce vomiting only if advised by physician or Poison Control Center. CALL PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

**Skin contact** Immediately flush skin with plenty of water while removing contaminated clothing.

**Eye contact** Immediately flush eyes with plenty of cool water for at least 15 minutes. Do NOT permit victim to rub eyes. GET MEDICAL ATTENTION IMMEDIATELY.

**Inhalation** Immediately remove victim to fresh air. If victim has stopped breathing give artificial respiration, preferably mouth-to-mouth. GET MEDICAL ATTENTION IMMEDIATELY.

#### Most important symptoms/effects, acute and delayed

**Inhalation** Cough, dizziness, headache

**Skin contact** Dry skin

**Eye contact** Redness, pain

### 5. Fire-fighting measures

**Suitable extinguishing media** Water spray, carbon dioxide, foam or dry chemical.

**Unsuitable extinguishing media** Straight stream

**Specific hazards arising from the chemical** To prevent possible storage container rupture, do not permit to freeze. Incompatible with strong acids, oxidizers, bases and chromium trioxide, potassium permanganate, and sodium peroxide.

SDS No. 0235011-US2  
 Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

**Special protective equipment and precautions for fire-fighters.** Wear suitable protective equipment such as gas mask, groves, etc.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

**Environmental precautions** The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

**Methods and materials for containment and cleaning up** Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. For disposal see section 13.

## 7. Handling and storage

**Precautions for safe handling.** Do not expose children and pets to this material.  
 After handling product, wash thoroughly with soap and water before drinking, eating, or smoking.  
 Keep away from open flames.

**Conditions for safe storage, including any incompatibilities** To prevent possible storage container rupture, do not permit to freeze.  
 Incompatible with strong acids, oxidizers, bases and chromium trioxide, potassium permanganate, and sodium peroxide.

## 8. Exposure controls/personal protection

### Control parameters

Component	CAS No.	Source	Exposure Limit	Notes
Ethylene glycol	107-21-1	US OSHA	None	None
		US ACGIH	100 mg/m <sup>3</sup> TLV	Ceiling Limit for Aerosols Only; A4 - Not classifiable as a human carcinogen

**Appropriate engineering controls** Handle in the presence of adequate ventilation. Engineering controls should be used whenever feasible to maintain concentrations below acceptable exposure criteria, including enclosures and local exhaust ventilation.

SDS No. 0235011-US2  
 Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

#### Individual protection measures, such as personal protective equipment

<b>Respiratory protection</b>	Where exposure is likely to exceed acceptable criteria and engineering controls are not feasible, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air and in accordance with OSHA (29 CFR 1910.134)
<b>Protective clothing</b>	Wear gloves and protective clothing which are impervious to the product for the duration of exposure if there is potential for skin contact.
<b>Eye protection</b>	Wear safety glasses meeting the specifications of ANSI Standard Z87.1 where no contact with the eye is anticipated. Chemical safety goggles meeting the specification of ANSI Standard Z87.1 should be worn whenever there is the possibility of splashing or other contact with the eyes.

## 9. Physical and chemical properties

<b>Appearance</b>	Clear, slightly viscous, blue liquid
<b>Odor</b>	No characteristic odor
<b>Odor threshold</b>	Not available
<b>pH</b>	7.9(Original)
<b>Freezing point</b>	-36°C
<b>Initial boiling point and boiling range</b>	108°C
<b>Flash point</b>	None
<b>Evaporation rate</b>	Not available
<b>Flammability(Solid, gas)</b>	Not available
<b>Upper/Lower flammability or explosive limits</b>	Not available
<b>Vapor pressure</b>	Not determined
<b>Vapor Density (Air = 1)</b>	Not determined
<b>Density (20°C)</b>	1.075 g/cm <sup>3</sup>
<b>Solubility in Water</b>	Infinite miscibility
<b>Partition coefficient n-octanol/water</b>	Not available
<b>Auto ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	Not available

## 10. Stability and reactivity

<b>Chemical stability</b>	Generally stable
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition.

SDS No. 0235011-US2  
Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

<b>Incompatible materials</b>	Not determined.
<b>Hazardous decomposition products</b>	If pyrolyzed, thermal decomposition products of residue may include C, CO, CO <sub>2</sub> , H <sub>2</sub> O, NH <sub>3</sub> , organic vapors and nitrogen-containing.

## 11. Toxicological information

<b>Inhalation</b>	Breathing excessive levels of the vapor or mist can irritate the respiratory tract. Excessive vapor concentrations of the major component (ethylene glycol), as might be generated during heating of this material, have occasionally been reported to cause adverse effects on the blood-forming system and the nervous system.
<b>Ingestion</b>	The acute oral toxicities of the main components of this mixture are as follows <u>Ethylene Glycol</u> The lowest dose reported to produce death in humans was estimated to be 1,560 mg/kg body weight; for a person weighing 150 pounds, this would be equivalent to drinking about three fluid ounces of pure ethylene glycol in a short period of time. Acute oral LD50's = 4,700 mg/kg (rats) 5,500 mg/kg (mouse)
<b>Eye contact :</b>	Based on the pH and irritation potential of this mixture's constituents, the mist or liquid can be expected to cause mild to moderate irritation or inflammation of the eyes
<b>Skin contact</b>	The acute dermal LD50 of the major component (ethylene glycol) of this product is 10,600mg/kg(rabbits). Based on the pH and the irritation potential of this mixture's constituents, the mist or liquid can be expected to cause mild to moderate irritation of the skin.
<b>Chronic effects</b>	No chronic or delayed effects have been identified IARC: No component of this product is present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. NTP: No component of this product is present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product is present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## 12. Ecological information

<b>Ecotoxicity</b>	
Ecological information of the product	<u>Ethylene Glycol</u> LC50 - Oncorhynchus mykiss (rainbow trout) - 18,500 mg/l - 96 h
<b>Persistence and degradability</b>	Degradation half life readily biodegradable
<b>Bioaccumulative potential</b>	Bioaccumulative potential Bioconcentration potential is low. Comments to bioaccumulation Log Pow: -0,30

SDS No. 0235011-US2  
 Product Name : Suzuki Super Long Life Coolant

Issue Date : December 10, 2015

**Mobility in soil** Mobility The product is miscible with water. May spread in water systems.

**Other adverse effects** Remarks None known.

### 13. Disposal considerations

**Waste Disposal** Disposal should be made in accordance with applicable federal, state and local regulations. All recovered material should be packaged, labeled, transported, and disposed of or reclaimed in conformance with good engineering practices. Avoid land filling of liquids. Reclaim where possible.

### 14. Transport information

**UN number** Not regulated

**Packing group** Not applicable

**Sea Transport(IMDG)** Not regulated

**Air Transport(IATA)** Not regulated

**Department of transportation(DOT)** Not regulated

### 15. Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

**Toxic Substance Control Act** This product is a mixture : therefore, it is not listed in the TSCA Inventory of Chemical Substances. All of the components of the mixture are listed in the TSCA Inventory of Chemical Substances.

**SARA Hazard Categories (as defined in Section 311/312)**

Health  
 Immediate (Acute) and Delayed (Chronic)

Physical  
 None.

The product contains ethylene glycol (CAS# 107-21-1) which is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

### 16. Other information

**NFPA Rating** Health (1) Fire (0) Reactivity (0)

The information presented herein is believed to be factual as it has been derived from the works and opinions of people believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which CCI CORPORATION bears legal responsibility. The user should review any recommendation in the specific context of intended use to determine whether they are appropriate.

## [会社情報]

販売者：(株)スズキ自販茨城

所在地：茨城県水戸市平須町1880-1

TEL:029-305-3511